

INDUSTRIAL LIGHTING LUMINAIRE SERIESSES EXPROOF LUMINARIES

KARIA-E




Technical Specifications

| | |
|-------------------|---------------------------------|
| Gövde | : Aluminum Extrusion |
| Işık Kaynağı | : Mid Power Led |
| Giriş Gerilimi | : 220-240V AC 50/60Hz |
| CRI | : >80 |
| IP | : IP65 |
| Difüzör | : Acrylic |
| Renk Sıcaklığı | : 3000K / 4000K / 5000K / 6500K |
| Çalışma Sıcaklığı | : -40°C ... +55°C |
| Gövde Rengi | : Ral 1023 |

| DIMENSIONS | POWER | LUMEN | WEIGHT |
|------------|-------|----------|--------|
| 52cm | 18W | 2.361lm | 1,8kg |
| 102cm | 30W | 3.792lm | 2,5kg |
| 102cm | 42W | 5.261lm | 2,5kg |
| 68cm | 75W | 10.650lm | 2kg |
| 100cm | 105W | 14.910lm | 2,8kg |
| 133cm | 140W | 19.880lm | 3,6kg |

Photometric Data



Technical Drawing



Options

| | |
|----------------|----------------|
| Driver | : Dali / 1-10V |
| Emergency Kit: | 1 hr / 3 hr |

Technical values have $\pm 5\%$ tolerance.